

Product Specifications		W2200PD
Product Model	W2200PD	
Panel Size / Type	22" Wide Aspect Color LCD TFT Active Matrix	
Pixel Dimension	0.282mm x 0.282mm	
Native / Optimum Resolution	1680 x 1050 @ 60Hz	
Maximum Resolution	1680 x 1050	
Response Time	5ms	
Contrast Ratio	700:1 (typical)	
Brightness	300 cd/m ²	
Viewing Angles	Horizontal: 160° Vertical: 160°	
Display Colors	16.7 Million Colors (8 bit)	
Active Display Area (H x V)	18.65" x 11.7" (473.8mm x 296.1mm)	
Aspect Ratio	16:10	
Input Signal	Horizontal: 31kHz~81kHz Vertical: 50Hz~75Hz	
Input PC Module	D-Sub x 15-pin (Analog RGB Input) DVI-Digital 24-pin Audio In 3.5mm headphone jack	
Input Video Module	N/A	
Audio	1W x 2 Stereo Speakers	
Compatible Signals	1680 x 1050 @ 60Hz 1440 x 900 @ 60Hz VESA 1280 x 1024 @ 72/70/60Hz VESA 1024 x 768 @ 75/70/60Hz VESA 800 x 600 @ 75/72/60/56Hz VESA 640 x 480 @ 75/60Hz, Super VGA, VGA 720 x 400 @ 70Hz Mac up to 1440 x 900	
HD Compatible	N/A	
Controls	Front Panel Controls: Power / Menu, Adjustment +/- 5 button OSD controls: Contrast, Brightness, Volume, Auto Adjust, H-V Position, Language, Frequency, Phase, Color, Recall, Exit	
Plug & Play (PnP)	VESA DDC 1/2B compliance	
VESA Mounting Holes	100 x 100 (mm)	
Base/Stand	Tilt: 5° Forward, 20° Backward	
Dimensions (W x H x D)	20.3" x 16.4" x 8.3" with stand (513.8mm x 417.5mm x 211.8mm)	
Box Dimensions (W x H x D)	22.1" x 19.3" x 5.5" (560mm x 490mm x 140mm)	
Weight	Net: 12.4 lbs., 5.6 kg Gross: 14.8 lbs., 6.7 kg	
Power Supply	Internal Input AC: 100 ~ 240 V, 47/63Hz	
Power Consumption	On: <55W Active Off: <2W	
Power Management / Agency Approvals	EPA Energy Star® Compliant / FCC(B) / UL / CE Energy Star / RoHS / TCO'99	
Part # / UPC	14MP2209A00 / 663555007315	
Environmental Conditions	Operating Temperature: 41° to 104° (5°C to 40°C) Operating Humidity: 20% to 80% (no condensation)	
Warranty	2 Years Limited Warranty	



W2200PD

PD Series



184 Technology Drive West
Irvine, CA 92618

Telephone: (949) 777-3379

Fax: (949) 777-3370

www.princetongraphics.com